

PRODUCT DATA SHEET

Figure:



IntraProfil UA 50
IntraProfil UA 75
IntraProfil UA 100
IntraProfil UA 125
IntraProfil UA 150

Technical data	
Material quality	Galvanized sheet steel according to EN 10143 and EN 10346, Zinc at least 100 g/m ² two-sided (Z100), material: 1.0226, quality DX51D+Z100, tensile strength ≥ 270 MPa (N/mm ²)
Material thickness	2,0 mm $\pm$ 0,14
Web height	UA 50 48.8 mm UA 75 73.8 mm UA 100 98.8 mm UA 125 123.8 mm UA 150 148.8 mm
Flange width	40 mm
Corrosion protection	At least 100 g/m ² two-sided (Z100)
Conformity	DIN 18182-1; EN 14195
Punch-outs	Round perforation $\varnothing$ 8 mm Long perforation 8.2 x 40mm
Building material class	A 1 - non-combustible
Product description	IntraProfil UA profiles are made of galvanized quality steel according to EN 10346 and are used to create ceiling / wall structures in the interior. Conformity to DIN 18182-1 and EN 14195 is certified.

This product data sheet corresponds to the current level of development. The suitability of the products cannot take into account the special aspects of the individual case and are provided without any warranty. Warranty and liability are subject to our general conditions for delivery. All details are given without guarantee.

IntraProfil Bausysteme GmbH

Am Wald 7

97348 Rödelsee

www.intraprofil.de Phone: 09323-8748-0

Rödelsee, 13.02.2023

Czasch, managing director

IntraProfil
Bausysteme