






**PROFILE nach DIN EN 18182-1 / DIN EN 14195**

Art.-Nr.	Bezeichnung	Material- dicke	Gewicht pro % lfm	Länge in cm	Gebinde KB / GB	EURO pro % lfm	
	<b>UD-Randprofile</b>						
	12030	UD 28 / 27	0,6 mm	38 kg	<b>300</b>	16 / 336	<b>174,00</b>
	12099	UD 28 / 27	0,6 mm	38 kg	<b>Fixlänge</b>	16 / 336	<b>174,00</b>
	<b>UD-Anschlussprofil</b>						
12130	UD 28 / 48	0,6 mm	47 kg	<b>300</b>	16 / 320	<b>243,00</b>	
12199	UD 28 / 48	0,6 mm	47 kg	<b>Fixlänge</b>	16 / 320	<b>243,00</b>	
	<b>CD-Deckenprofil</b>						
	10019	CD 60 / 27 „rund-glatt“	0,6 mm	58 kg	<b>119</b>	12 / 180	<b>295,00</b>
	10026	CD 60 / 27 „rund-glatt“	0,6 mm	58 kg	<b>260</b>	12 / 180	<b>243,00</b>
	10031	CD 60 / 27 „rund-glatt“	0,6 mm	58 kg	<b>310</b>	12 / 180	<b>243,00</b>
	10040	CD 60 / 27 „rund-glatt“	0,6 mm	58 kg	<b>400</b>	12 / 180	<b>243,00</b>
10099	CD 60 / 27 „rund-glatt“	0,6 mm	58 kg	<b>Fixlänge</b>	12 / 180	<b>243,00</b>	
 	<b>UW-Randprofile</b>						
	12240	UW 50 / 40	0,6 mm	60 kg	<b>400</b>	8 / 160	<b>247,00</b>
	12299	UW 50 / 40	0,6 mm	60 kg	<b>Fixlänge</b>		<b>247,00</b>
	12440	UW 75 / 40	0,6 mm	71 kg	<b>400</b>	8 / 120	<b>287,00</b>
	12499	UW 75 / 40	0,6 mm	71 kg	<b>Fixlänge</b>		<b>287,00</b>
	12640	UW 100 / 40	0,6 mm	82 kg	<b>400</b>	8 / 80	<b>336,00</b>
	12699	UW 100 / 40	0,6 mm	82 kg	<b>Fixlänge</b>		<b>336,00</b>
	12740	UW 125 / 40	0,6 mm	94 kg	<b>400</b>	8 / 80	<b>426,00</b>
	12799	UW 125 / 40	0,6 mm	94 kg	<b>Fixlänge</b>		<b>426,00</b>
	12840	UW 150 / 40	0,6 mm	106 kg	<b>400</b>	8 / 80	<b>504,00</b>
12899	UW 150 / 40	0,6 mm	106 kg	<b>Fixlänge</b>		<b>504,00</b>	
	<b>vorgestanzte Profile</b>						
	13225	UD 28 / 27	0,6 mm	38 kg	<b>250</b>	4	<b>523,00</b>
	13325	UW 50 / 40	0,6 mm	60 kg	<b>250</b>	4	<b>731,00</b>
	13425	UW 75 / 40	0,6 mm	71 kg	<b>250</b>	4	<b>900,00</b>
13625	UW 100 / 40	0,6 mm	82 kg	<b>250</b>	4	<b>1.022,00</b>	